

CleanLine™

High Durability Polyethylene Tubing

SUPERIOR STRESS & CRACK RESISTANCE
IMPERMEABLE TO GASSES & MOISTURE
GREATER TENSILE STRENGTH
TASTELESS & ODORLESS
HIGH BURST PRESSURE
PUNCTURE RESISTANT

CleanLine™ High Durability Polyethylene Tubing

CleanLine™ is a linear, low-density polyethylene tubing that is tasteless and odorless, making it suitable for beverage dispensing and fresh water systems. Its high-strength properties and color availability also make it the tubing of choice for the carwash industry. CleanLine™ is compatible with quick push-to-connect fittings and may be used with pneumatic controlled machinery and color-coded liquid or gas supply lines. It features superior puncture, stress and crack resistance and can withstand high burst pressure. CleanLine™ additionally has exceptional dielectric properties and is impermeable to gasses and moisture.

**Available in a range of colors for easy identification
& color coding!**



Sizing Chart

Part Number	ID	OD	Wall	Std. Length
TT-LLD0.170-0.250BL	0.170"	.250"	.04"	100'
TT-LLD0.170-0.250PK	0.170"	.250"	.04"	100'
TT-LLD0.500-0.625BK	0.500"	.625"	.0625"	100'
TT-LLD0.500-0.625PP	0.500"	.625"	.0625"	100'
TT-LLD0.250-0.375CL	0.250"	.375"	.0625"	100'
TT-LLP.250-.375GD	0.250"	.375"	.0625"	100'
TT-LLP.250-.375OR	0.250"	.375"	.0625"	100'
TT-LLP.250-.375PK	0.250"	.375"	.0625"	100'
TT-LLP.250-.375TQ	0.250"	.375"	.0625"	100'

*Contact your account representative for custom sizes and colors.

Applications

Carwashes
Beverage Dispensing
Fresh water systems
Pneumatic Controlled Machinery
Color coded liquid/gas supply lines

Benefits

Greater tensile strength
High burst pressure
Superior stress and crack resistance
Tasteless and odorless
Puncture resistance
Impermeable to gasses and moisture
Superior dielectric properties
Works with quick push-to-connect fittings

